



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9952 - 15 Watt PLL LED; 2G11 Base; 2000 Lumens; 120-277 Volt; 3500K; Type B; Ballast Bypass



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V-277V
Lumens:	1900L
CRI:	80+
CCT (Kelvins):	3500K - Neutral White
Beam Spread :	270
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	36W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	20% (+/-5%)
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923099526
Each Quantity:	1
Each Dimensions:	16.80 x 1.50 x 0.69

INFO

Additional Info:	CCT Selectable Option: S18422
Installation Note:	Not for use in vapor tight fixtures.

PHYSICAL

Base:	4-Pin
Shape:	T5
Finish:	Frost
Dimensions (In.):	MOL: 16.5 - MOD: 0.68
Weight (Lbs.):	0.31
Material:	Glass / Thermo Plastic (PBT) Cap
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTE21CJTEN000079
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S9952 - 15 Watt PLL LED; 2G11 Base; 2000 Lumens; 120-277 Volt;
3500K; Type B; Ballast Bypass

ACCESSORIES

	S8000	5 Watt LED Emergency Driver; 120-277 Volts
--	--------------	--

	S8002	10 Watt LED Emergency Driver; 120-277 Volt
--	--------------	--
