



Project/Job Name:

Location:

Fixture Type:

Notes:

S9953 - 15 Watt PLL LED; 2G11 Base; 2000 Lumens; 120-277 Volt; 4000K; Type B; Ballast Bypass



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V-277V
Lumens:	2000L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	270
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	36W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	20% (+/-5%)
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923099533
Each Quantity:	1
Each Dimensions:	0.75 x 1.75 x 16.75

INFO

Additional Info:	CCT Selectable Option: S18422
Installation Note:	Not for use in vapor tight fixtures.



S9953 - 15 Watt PLL LED; 2G11 Base; 2000 Lumens; 120-277 Volt; 4000K; Type B; Ballast Bypass

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
