



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9968 - 4.5 Watt G30 LED Filament; Amber; Medium base; 2000K; 240 Lumens; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	4.5W
Volts:	120V
Lumens:	240L
CRI:	80+
CCT (Kelvins):	2000K -
Beam Spread :	360
Hours Rated:	15000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Reverse Phase or Phase Selectable
Incandescent Equivalent :	25W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Operating Position:	Universal
Light Source:	LED Filament
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923099687
Each Quantity:	1
Each Dimensions:	3.94 x 3.94 x 6.10

PHYSICAL

Base:	Medium
Shape:	G30
Finish:	Transparent Amber
Lens Finish:	Transparent Amber
Dimensions (In.):	MOL: 5.44 - MOD: 3.75
Weight (Lbs.):	0.13
Material:	Glass
Housing Color:	None

COMPLIANCE

Safety Listing:	cULus
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NOM-030-ENER-2016!NTEC22EN003836
NOM Expiration Date:	5/29/2024
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

ROI Category:	Screw
---------------	-------



S9968 - 4.5 Watt G30 LED Filament; Amber; Medium base; 2000K;
240 Lumens; 120 Volt

DIMMER COMPATIBILITY

Lutron	CTRP-253P
Lutron	DVRP-253P
Lutron	NTRP-250
Lutron	RRD-PRO