



ELECTRICAL

Technology:	LED
Watts:	14W
Volts:	120V-277V
Lumens:	1400L
CRI:	80+
CCT (Kelvins):	27K/40K/50K - Warm White to Natural Light
Beam Spread :	320
Hours Rated:	15000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	22W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	<20%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	Range Voltage
Warranty:	2-Years

Project/Job Name:

Location:

Fixture Type:

Notes:

S11545 - 14 Watt LED PL; 27K/4K/5K CCT Selectable; GX32d-2 Base; 22W CFL Replacement; Type B Ballast Bypass; 120-277 Range Voltage

- CCT Selectable



PHYSICAL

Base:	2-Pin
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 6.3 - MOD: 1.93
Weight (Lbs.):	0.3
Material:	Aluminum / Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cETLus - Classified
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Open Rated Lamp
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
IP Rating:	IP20
RoHS Compliant:	Yes
Restrictions:	No Restrictions

PACKAGING

Each UPC:	045923115455
Each Quantity:	1
Each Dimensions:	2.09 x 2.09 x 6.50



S11545 - 14 Watt LED PL; 27K/4K/5K CCT Selectable; GX32d-2 Base; 22W CFL Replacement; Type B Ballast Bypass; 120-277 Range Voltage

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
