



#### ELECTRICAL

Technology:	LED
Watts:	18W
Volts:	120V-277V
Lumens:	1800L
CRI:	80+
CCT (Kelvins):	27K/40K/50K - Warm White to Natural Light
Beam Spread :	320
Hours Rated:	15000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	28W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	<20%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	Range Voltage
Warranty:	2-Years

Project/Job Name:

Location:

Fixture Type:

Notes:

**S11546** - 18 Watt LED PL; 27K/4K/5K CCT Selectable; GX32d-3

Base; 28W CFL Replacement; Type B Ballast Bypass; 120-277 Range Voltage

- CCT Selectable



#### PHYSICAL

Base:	2-Pin
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 6.89 - MOD: 1.93
Weight (Lbs.):	0.32
Material:	Aluminum / Plastic
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cETLus - Classified
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Open Rated Lamp
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
IP Rating:	IP20
RoHS Compliant:	Yes
Restrictions:	No Restrictions

#### PACKAGING

Each UPC:	045923115462
Each Quantity:	1
Each Dimensions:	2.09 x 2.09 x 7.09



**S11546** - 18 Watt LED PL; 27K/4K/5K CCT Selectable; GX32d-3 Base; 28W CFL Replacement; Type B Ballast Bypass; 120-277 Range Voltage

## ACCESSORIES

---



**S8000** 5 Watt LED Emergency Driver; 120-277 Volts

---



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt

---