



ELECTRICAL

Technology:	LED
Watts:	3.5W
Volts:	120V-277V
Lumens:	380L/390L/400L/410L
CRI:	80+
CCT (Kelvins):	27K/30K/35K/40K - Warm to Cool White
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	5W/7W/9W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

Project/Job Name:

Location:

Fixture Type:

Notes:

S11555 - 3.5 Watt; 2G7 Base; 27K/30K/35K/40K CCT Selectable; Frost Finish; Ballast Bypass; 120-277 Volt

- CCT Selectable



PHYSICAL

Base:	4-Pin
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 4.74 - MOD: 1.26
Weight (Lbs.):	0.06
Material:	Polycarbonate (PC)
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Open Rated Lamp
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

PACKAGING

Each UPC:	045923115554
Each Quantity:	1
Each Dimensions:	1.54 x 0.91 x 4.84



S11555 - 3.5 Watt; 2G7 Base; 27K/30K/35K/40K CCT Selectable;
Frost Finish; Ballast Bypass; 120-277 Volt

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
