



#### ELECTRICAL

Technology:	LED
Watts:	5.5W
Volts:	120V-277V
Lumens:	600L/620L/630L/650L
CRI:	80+
CCT (Kelvins):	27K/30K/35K/40K - Warm to Cool White
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	13W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

Project/Job Name:

Location:

Fixture Type:

Notes:

**S11556** - 5.5 Watt; 2GX7 Base; 27K/30K/35K/40K CCT Selectable; Frost Finish; Ballast Bypass; 120-277 Volt

- CCT Selectable



#### PHYSICAL

Base:	2GX7 (4-Pin)
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 6.51 - MOD: 1.26
Weight (Lbs.):	0.08
Material:	Polycarbonate (PC)
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Classified
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Open Rated Lamp
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

#### PACKAGING

Each UPC:	045923115561
Each Quantity:	1
Each Dimensions:	1.54 x 0.91 x 6.61



**S11556** - 5.5 Watt; 2GX7 Base; 27K/30K/35K/40K CCT Selectable; Frost Finish; Ballast Bypass; 120-277 Volt

## ACCESSORIES

---



**S8000** 5 Watt LED Emergency Driver; 120-277 Volts

---



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt

---