



#### ELECTRICAL

|                           |  |
|---------------------------|--|
| Technology:               | LED  |
| Watts:                    | 15W  |
| Volts:                    | 120V-277V                                    |
| Lumens:                   | 2000L  |
| CRI:                      | 80+  |
| CCT (Kelvins):            | 35K/40K/50K - Neutral White to Natural Light |
| Beam Spread :             | 140  |
| Hours Rated:              | 50000  |
| Dimmable:                 | Non-Dimmable -                               |
| Fluorescent Equivalent :  | 32W  |
| Operating Temperature :   | 0C (+32F) to +45C (+113F)                    |
| Ballasting Requirements : | Ballast Bypass                               |
| Lamp Ballast Type A/B/C : | Type B                                       |
| THD:                      | <25%   |
| Light Source:             | LED  |
| Voltage Type:             | Range Voltage                                |
| Battery Chemistry:        | Lithium-ion (Li-ion)                         |
| Warranty:                 | 5-Years                                      |

#### PACKAGING

|                  |                     |
|------------------|---------------------|
| Each UPC:        | 045923117329        |
| Each Quantity:   | 1                   |
| Each Dimensions: | 51.57 x 1.38 x 1.38 |

#### INFO

|                     |  |
|---------------------|--|
| Additional Info:    | 3.5 Watts and 500 Lumens in Emergency Mode                                   |
| Specification Note: | Work time after power failure: 90 Minutes; Battery Recharge Time is 24 hours |
| Installation Note:  | Not for use in vapor tight fixtures. Maximum Mounting Height: 13 Feet        |
| Tube Guard Use:     | FALSE  |

Project/Job Name:

Location:

Fixture Type:

Notes:

**S11732** - 15 Watt T8 LED; 48 Inch; 35K/40K/50K CCT Selectable; Medium Bi Pin Base; Type B Ballast Bypass; 120-277V

- CCT Selectable



#### PHYSICAL

|                   |                               |
|-------------------|-------------------------------|
| Base:             | Medium Bi Pin                 |
| Shape:            | T8                            |
| Finish:           | Frost                         |
| Dimensions (In.): | MOL: 47.78 - MOD: 1.16        |
| Nominal Length:   | 48                            |
| Weight (Lbs.):    | 1.12                          |
| Material:         | Aluminum / Polycarbonate (PC) |
| Leg Spacing:      | 0.51                          |

#### COMPLIANCE

|                             |  |
|-----------------------------|--|
| Safety Listing:             | cRUs - Recognized Component; cULUs - Certified; cULUs - Classified |
| Location Rating:            | Damp   |
| Indoor/Outoor:              | Indoor   |
| DLC Approved:               | Yes  |
| DLC Classification:         | Standard   |
| DLC ID:                     | S-ZM2STB   |
| BAA Compliant:              | No   |
| Enclosure Rating:           | Enclosed Rated Lamp  |
| Rated For Enclosed Fixture: | Yes  |
| FCC Compliant:              | Yes  |
| IP Rating:                  | IP20   |
| NSF Approved:               | Yes  |
| RoHS Compliant:             | Yes  |
| Restrictions:               | No Restrictions  |



**S11732** - 15 Watt T8 LED; 48 Inch; 35K/40K/50K CCT Selectable;  
Medium Bi Pin Base; Type B Ballast Bypass; 120-277V

## ACCESSORIES

---



**S11733**

Emergency Remote Test Switch For S11732; 9" Leads

---