



Project/Job Name:

Location:

Fixture Type:

Notes:

S11742R1 - 9.5 Watt; 4 Foot T8 LED; G13 Base; 4000K; Type A



ELECTRICAL

| | |
|---------------------------|--|
| Technology: | LED |
| Watts: | 9.5W |
| Volts: | Ballast Dependent |
| Lumens: | 1740L |
| CRI: | 80+ |
| CCT (Kelvins): | 4000K - Cool White |
| Beam Spread : | 210 |
| Hours Rated: | 50000 |
| Dimmable: | Yes-Dimmable - Only in Type A mode; Check Ballast MFG for Dimmer Compatibility |
| Dimmable Down To %: | 100 to 20 percent |
| Incandescent Equivalent : | 75W |
| Fluorescent Equivalent : | 32W/30W/28W/25W |
| Operating Temperature : | -20C (-4F) to +45C (+113F) |
| Ballasting Requirements : | Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart |
| Lamp Ballast Type A/B/C : | Type A |
| THD: | 20% |
| Power Factor : | 0.9 |
| Light Source: | LED |
| Voltage Type: | Ballast Dependent |
| Warranty: | 5-Years |

PACKAGING

| | |
|------------------|---------------------|
| Each UPC: | 045923402937 |
| Each Quantity: | 1 |
| Each Dimensions: | 48.00 x 1.10 x 1.10 |

INFO

| | |
|--------------------|--------------------------------------|
| Installation Note: | Not for use in vapor tight fixtures. |
|--------------------|--------------------------------------|