



Project/Job Name:

Location:

Fixture Type:

Notes:

S11757 - 24/32/40 Wattage Selectable; 30/35/40/50/65K CCT Selectable; 8 Foot LED; Fa8 Base; 120-277 Volt; 2-pc

- Wattage Selectable

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	24W/32W/40W
Volts:	120V-277V
Lumens:	3500L/4400L/5500L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	210
Hours Rated:	50000
Incandescent Equivalent :	100W
Fluorescent Equivalent :	59W/86W/96W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	<25%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923117572
Each Quantity:	1
Each Dimensions:	48.46 x 2.68 x 1.42

PHYSICAL

Base:	Single Pin
Shape:	T8
Finish:	White
Dimensions (In.):	MOL: 93.75 - MOD: 1
Nominal Length:	96
Weight (Lbs.):	0.98
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-J3JX31
BAA Compliant:	No
Enclosure Rating:	Not for use in fully enclosed vapor tight fixtures
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Shatterproof Type:	PET Coated
Includes:	(1) Set R17d Endcaps; (1) C-Clip



S11757 - 24/32/40 Wattage Selectable; 30/35/40/50/65K CCT Selectable; 8 Foot LED; Fa8 Base; 120-277 Volt; 2-pc

ACCESSORIES



S8002

10 Watt LED Emergency Driver; 120-277 Volt
