



Project/Job Name:

Location:

Fixture Type:

Notes:

S11758 - 24/32/40 Watt T8 LED; 30K/35K/40K/50K/65K CCT

Selectable; 8 Foot; Ballast Bypass; Fa8 Base; 120-277 Volt

- Wattage Selectable

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	24W/32W/40W
Volts:	120V-277V
Lumens:	3500L/4400L/5500L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	210
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	59W/86W/96W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	<25%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923117589
Each Quantity:	1
Each Dimensions:	95.87 x 7.56 x 3.86

INFO

Specification Note:	Not for use in fully enclosed vapor tight fixtures
Shatterproof Type:	PET Coated
Includes:	(1) Set R17d & Fa8 Endcaps



S11758 - 24/32/40 Watt T8 LED; 30K/35K/40K/50K/65K CCT
Selectable; 8 Foot; Ballast Bypass; Fa8 Base; 120-277 Volt

ACCESSORIES



S8002

10 Watt LED Emergency Driver; 120-277 Volt
