



Project/Job Name:

Location:

Fixture Type:

Notes:

**S12142** - 2 Watt Prismatic HX11 LED; 2700K CCT; Candelabra Base; 120 Volt; Aurora Finish; 2-Card



#### ELECTRICAL

|                           |                                                    |
|---------------------------|----------------------------------------------------|
| Technology:               | LED                                                |
| Watts:                    | 2W                                                 |
| Volts:                    | 120V                                               |
| Lumens:                   | 150L                                               |
| CRI:                      | 80+                                                |
| CCT (Kelvins):            | 2700K - Warm White                                 |
| Beam Spread :             | 360                                                |
| Hours Rated:              | 15000                                              |
| Dimmable:                 | Yes-Dimmable - 120V only                           |
| Dimmable Down To %:       | 100 to 10 percent                                  |
| Dimming Type :            | Forward Phase or Reverse Phase or Phase Selectable |
| Incandescent Equivalent : | 25W                                                |
| Operating Temperature :   | -20C (-4F) to +45C (+113F)                         |
| Power Factor :            | >0.5                                               |
| Light Source:             | LED                                                |
| Voltage Type:             | AC Only                                            |
| Warranty:                 | 2-Years                                            |

#### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923121425       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 5.31 x 1.26 x 7.87 |

#### PHYSICAL

|                   |                       |
|-------------------|-----------------------|
| Base:             | Candelabra            |
| Shape:            | HX11                  |
| Finish:           | Aurora                |
| Dimensions (In.): | MOL: 4.73 - MOD: 1.26 |
| Weight (Lbs.):    | 0.03                  |
| Material:         | Glass                 |
| Housing Color:    | Clear                 |

#### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Listed |
| Location Rating:            | Damp                              |
| Indoor/Outdoor:             | Indoor                            |
| DLC Approved:               | No                                |
| BAA Compliant:              | No                                |
| Enclosure Rating:           | Enclosed Rated Lamp               |
| Rated For Enclosed Fixture: | Yes                               |
| FCC Compliant:              | Yes                               |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | Not For Sale In: CA               |



**S12142** - 2 Watt Prismatic HX11 LED; 2700K CCT; Candelabra Base; 120 Volt; Aurora Finish; 2-Card

#### DIMMER COMPATIBILITY

|         |           |
|---------|-----------|
| Leviton | 66ELV     |
| Satco   | 80/2699   |
| Satco   | 80/2700   |
| Satco   | 80/2701   |
| Satco   | 80/2702   |
| Satco   | 80/2703   |
| Satco   | 80/2704   |
| Satco   | 86/103    |
| Lutron  | CTRP-253P |
| Leviton | DDL06     |
| Leviton | DDMX1     |
| Leviton | DG6HD     |
| Leviton | DH6HD     |
| Leviton | DL6HD     |
| Leviton | DSE06-10Z |
| Leviton | DSL06     |
| Leviton | DSM10     |
| Eaton   | DUL06P-C2 |
| Lutron  | DVRF-5NE  |
| Lutron  | DVRF-6L   |
| Lutron  | DVRP-253P |
| Leviton | DW6HD     |
| Leviton | DZ6HD     |
| Lutron  | HQR-3LD   |
| Lutron  | HQR-3PD   |

|        |          |
|--------|----------|
| Lutron | HQRA-PRO |
|--------|----------|

SATCO.COM | 800-437-2826

© Satco Products, Inc.  
All rights reserved 2026

|                  |              |
|------------------|--------------|
| <b>Lutron</b>    | HQRD-10D     |
| <b>Lutron</b>    | HQRD-10NBD   |
| <b>Lutron</b>    | HQRD-6CL     |
| <b>Lutron</b>    | HQRD-6ND     |
| <b>Lutron</b>    | HQRD-HN6BRL  |
| <b>Lutron</b>    | HQRD-PRO     |
| <b>Lutron</b>    | HRST-PRO-N   |
| <b>Lutron</b>    | MA-PRO       |
| <b>Lutron</b>    | MAELV-600    |
| <b>Precision</b> | MR42400PLS   |
| <b>Lutron</b>    | MRF2-3LD     |
| <b>Lutron</b>    | MRF2-3PD     |
| <b>Lutron</b>    | MRF2S-6ELV   |
| <b>Lutron</b>    | NTCL-250     |
| <b>Lutron</b>    | NTRP-250     |
| <b>Hubbell</b>   | NXFRD-UNV    |
| <b>Overdrive</b> | ODMR0205     |
| <b>Lutron</b>    | PD-10NXD     |
| <b>Lutron</b>    | PD-3PCL      |
| <b>Lutron</b>    | PD-5NE       |
| <b>Lutron</b>    | PD-6WCL      |
| <b>Lutron</b>    | PHPM-WBX-120 |
| <b>Leviton</b>   | REL06-WW     |
| <b>Eaton</b>     | RF9640-ND    |
| <b>Leviton</b>   | RNL06-10Z    |
| <b>Lutron</b>    | RRD-10D      |
| <b>Lutron</b>    | RRD-3LD      |
| <b>Lutron</b>    | RRD-3PD      |

|                |            |
|----------------|------------|
| <b>Lutron</b>  | RRD-6CL    |
| <b>Lutron</b>  | RRD-6ND    |
| <b>Lutron</b>  | RRD-H6BRL  |
| <b>Lutron</b>  | RRD-PRO    |
| <b>Lutron</b>  | RRST-PRO-N |
| <b>Satco</b>   | S11268     |
| <b>Satco</b>   | S11270     |
| <b>Eaton</b>   | SALo6P     |
| <b>Lutron</b>  | SELV-300P  |
| <b>Lutron</b>  | SLV-600P   |
| <b>Lutron</b>  | ST-PRO-N   |
| <b>Eaton</b>   | SUF7       |
| <b>Lutron</b>  | TGCL-153PH |
| <b>Leviton</b> | TSM10      |
| <b>Leviton</b> | VPEo6-1LZ  |
| <b>Eaton</b>   | VSULo6D    |
| <b>Acuity</b>  | WSX-PDT-WH |
| <b>Legrand</b> | WWRL50WH   |