



ELECTRICAL

Technology:	LED
Watts:	60W/45W/36W
Volts:	120V-277V
Lumens:	8700L-9600L/6525L-7200L/5220L-5760L
CRI:	80
CCT (Kelvins):	30K/40K/50K - Soft White to Natural Light
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only dimmable through wattage selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls.
Dimming Type :	Step Dimming
HID Equivalent :	200W-250W
Operating Temperature :	-25C (-13F) to +50C (+122F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Base Down
Surge Protection :	Built-in surge protection - 4KV
THD:	<20%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923131493
Each Quantity:	1
Each Dimensions:	7.68 x 7.68 x 7.91

Project/Job Name:

Location:

Fixture Type:

Notes:

S13149 - 60/45/36 Watt LED HID Replacement; 3K/4K/5K CCT Selectable; Ballast Bypass; Extended Mogul Base; 120-277 Range Voltage

- Wattage Selectable
- CCT Selectable



PHYSICAL

Base:	Mogul Extended
Shape:	Corncob
Finish:	Clear
Lens Finish:	Translucent
Lens Material:	Polycarbonate (PC)
Dimensions (In.):	MOL: 6.57 - MOD: 6.63
Weight (Lbs.):	1.36
Material:	Aluminum
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus
Location Rating:	Wet
Indoor/Outoor:	Indoor and Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-2R1YW3
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP65
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S13149 - 60/45/36 Watt LED HID Replacement; 3K/4K/5K CCT Selectable; Ballast Bypass; Extended Mogul Base; 120-277 Range Voltage

ACCESSORIES



80-929

LED HID Surge Protector; 100-277V AC; 10KV Protection Level
