



ELECTRICAL

Technology:	LED
Watts:	13.5W
Volts:	120V-277V
Lumens:	1700L
CRI:	80+
CCT (Kelvins):	2200K - Warm White
Beam Spread :	320
Hours Rated:	50000
Dimmable:	Non-Dimmable -
HID Equivalent :	50W
Operating Temperature :	-30C (-22F) to +65C (+149F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 4kV
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923131806
Each Quantity:	1
Each Dimensions:	2.56 x 2.56 x 6.89

INFO

Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 5.98 in. Width: 5.98 in. Height: 10.16 in.

Project/Job Name:

Location:

Fixture Type:

Notes:

S13180 - 13.5 Watt LED HID Replacement; ED17; 2200K; Medium Base; Clear; 120-277 Range Voltage



PHYSICAL

Base:	Medium
Shape:	ED17
Finish:	Clear
Dimensions (In.):	MOL: 5.8 - MOD: 2.13
Weight (Lbs.):	0.17
Material:	Glass
Housing Color:	Frost

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Wet
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP65
RoHS Compliant:	Yes
Restrictions:	Not For Sale In: CA



S13180 - 13.5 Watt LED HID Replacement; ED17; 2200K; Medium Base; Clear; 120-277 Range Voltage

ACCESSORIES



92-410

Mogul To Medium E39 - E26 Reducer; 660W; 600V
