



ELECTRICAL

Technology:	LED
Watts:	40W
Volts:	120V-277V
Lumens:	6000L
CRI:	80+
CCT (Kelvins):	3000K - Soft White
Beam Spread :	320
Hours Rated:	50000
Dimmable:	Non-Dimmable -
HID Equivalent :	170W
Operating Temperature :	-30C (-22F) to +65C (+149F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 4KV
THD:	<20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923131981
Each Quantity:	1
Each Dimensions:	3.94 x 3.94 x 9.45

INFO

Installation Note:	Not for use in vapor tight fixtures.
--------------------	--------------------------------------

Project/Job Name:

Location:

Fixture Type:

Notes:

S13198 - 40 Watt LED HID Replacement; ED28; 3000K CCT; Mogul Extended Base; 120-277 Range Voltage



PHYSICAL

Base:	Mogul Extended
Shape:	ED28
Finish:	White
Dimensions (In.):	MOL: 8.4 - MOD: 3.54
Weight (Lbs.):	0.41
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified; cULus - Listed
Location Rating:	Wet
Indoor/Outoor:	Indoor and Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-X48JV3
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP65
RoHS Compliant:	Yes
Restrictions:	No Restrictions