



ELECTRICAL

Technology:	LED
Watts:	4.5W
Volts:	120V-277V
Lumens:	450L/475L/500L/500L/475L
CRI:	80+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	360
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	5W/7W/9W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	<20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

Project/Job Name:

Location:

Fixture Type:

Notes:

S18405 - 4.5 Watt LED PL 2-PIN; G23 Base;
27K/30K/35K/40K/50K CCT Selectable; 120-277 Volt; Type B;
Ballast Bypass

- CCT Selectable



PHYSICAL

Base:	G23 (2-Pin)
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 6.5 - MOD: 1.27
Weight (Lbs.):	0.09
Material:	Polycarbonate (PC)
Housing Color:	White

COMPLIANCE

Safety Listing:	cETLus - Classified
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

PACKAGING

Each UPC:	045923184055
Each Quantity:	1
Each Dimensions:	1.46 x 0.98 x 6.89



S18405 - 4.5 Watt LED PL 2-PIN; G23 Base;
27K/30K/35K/40K/50K CCT Selectable; 120-277 Volt; Type B;
Ballast Bypass

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
