



#### ELECTRICAL

Technology:	LED
Watts:	11.5W/13W/15W
Volts:	120V-277V
Lumens:	1800L/2000L/2200L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	210
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Incandescent Equivalent :	50W
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Ballast Type A/B/C :	Type A/B
Lamp End Type :	Single Ended; Double Ended
THD:	<20%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923184147
Each Quantity:	1
Each Dimensions:	23.03 x 1.22 x 2.83

#### INFO

Installation Note:	Not for use in vapor tight fixtures.
--------------------	--------------------------------------

Project/Job Name:

Location:

Fixture Type:

Notes:

**S18414** - 11.5/13/15 Wattage Selectable T8 U-Bend LED; 30K/35K/40K/50K/65K CCT Selectable; 1-Inch; Frost Finish; 120-277 Range Voltage

• Wattage Selectable

• CCT Selectable



#### PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Frost
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 22.43 - MOD: 0.96
Weight (Lbs.):	0.5
Material:	Glass
Leg Spacing:	1.63
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-H5FJF9
BAA Compliant:	No
Enclosure Rating:	Open Rated Lamp
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



**S18414** - 11.5/13/15 Wattage Selectable T8 U-Bend LED;  
30K/35K/40K/50K/65K CCT Selectable; 1-Inch; Frost Finish;  
120-277 Range Voltage

## ACCESSORIES

---



**S8000** 5 Watt LED Emergency Driver; 120-277 Volts

---



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt

---