



#### ELECTRICAL

Technology:	LED
Watts:	8.5W
Volts:	120V-277V
Lumens:	930L/950L/980L/980L/980L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	115
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	18W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923184208
Each Quantity:	1
Each Dimensions:	10.20 x 1.89 x 0.94

#### INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated

Project/Job Name:

Location:

Fixture Type:

Notes:

**S18420** - 8.5 Watt PLL LED; 2G11 Base; 30K/35K/40K/50K/65K CCT Selectable; Ballast Bypass; 120-277 Volt

- CCT Selectable



#### PHYSICAL

Base:	4-Pin
Shape:	T5
Finish:	Frost
Dimensions (In.):	MOL: 8.9 - MOD: 1.72
Weight (Lbs.):	0.18
Material:	Glass
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



**S18420** - 8.5 Watt PLL LED; 2G11 Base; 30K/35K/40K/50K/65K  
CCT Selectable; Ballast Bypass; 120-277 Volt

## ACCESSORIES

---



**S8000** 5 Watt LED Emergency Driver; 120-277 Volts

---



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt

---