



ELECTRICAL

Technology:	LED
Watts:	10W
Volts:	120V-277V
Lumens:	1180L/1200L/1250L/1250L/1250L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	115
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	24W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923184215
Each Quantity:	1
Each Dimensions:	13.98 x 1.89 x 0.94

INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated

Project/Job Name:

Location:

Fixture Type:

Notes:

S18421 - 10 Watt PLL LED; 2G11 Base; 30K/35K/40K/50K/65K CCT Selectable; Ballast Bypass; 120-277 Volt

- CCT Selectable



PHYSICAL

Base:	4-Pin
Shape:	T5
Finish:	Frost
Dimensions (In.):	MOL: 12.7 - MOD: 1.72
Weight (Lbs.):	0.22
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S18421 - 10 Watt PLL LED; 2G11 Base; 30K/35K/40K/50K/65K
CCT Selectable; Ballast Bypass; 120-277 Volt

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
