



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S18423 - 20 Watt PLL LED; 2G11 Base; 30K/35K/40K/50K/65K
CCT Selectable; Ballast Bypass; 120-277 Volt

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	20W
Volts:	120V-277V
Lumens:	2650L/2700L/2800L/2800L/2800L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	140
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923184239
Each Quantity:	1
Each Dimensions:	23.50 x 1.89 x 0.94

INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated

PHYSICAL

Base:	4-Pin
Shape:	T5
Finish:	Frost
Dimensions (In.):	MOL: 22.5 - MOD: 1.72
Weight (Lbs.):	0.37
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S18423 - 20 Watt PLL LED; 2G11 Base; 30K/35K/40K/50K/65K
CCT Selectable; Ballast Bypass; 120-277 Volt

ACCESSORIES

	S8000	5 Watt LED Emergency Driver; 120-277 Volts
--	--------------	--

	S8002	10 Watt LED Emergency Driver; 120-277 Volt
--	--------------	--
