



ELECTRICAL

| | |
|---------------------------|------------------------------------------------------|
| Technology: | LED |
| Watts: | 5W |
| Volts: | 120V-277V |
| Lumens: | 630L |
| CRI: | 80+ |
| CCT (Kelvins): | 3500K - Neutral White |
| Beam Spread : | 300 |
| Hours Rated: | 50000 |
| Dimmable: | Non-Dimmable - |
| Fluorescent Equivalent : | 13W |
| Operating Temperature : | -20C (-4F) to +45C (+113F) |
| Ballasting Requirements : | Ballast required (Type A) or Ballast Bypass (Type B) |
| Lamp Ballast Type A/B/C : | Type A/B |
| Operating Position: | Universal |
| Power Factor : | 0.9 |
| Light Source: | LED |
| Voltage Type: | Range Voltage |
| Warranty: | 5-Years |

PACKAGING

| | |
|------------------|--------------------|
| Each UPC: | 045923409370 |
| Each Quantity: | 1 |
| Each Dimensions: | 1.77 x 1.77 x 4.21 |

INFO

| | |
|-----------------------|-------------------------------------------------|
| Min Compartment Size: | Length 6.10 in. Width 6.10 in. Height: 7.87 in. |
|-----------------------|-------------------------------------------------|

Project/Job Name:

Location:

Fixture Type:

Notes:

S21422 - 5 Watt; PL LED; GX23 Base; Frost Finish; Type A/B Dual Ballast; 3500K; 120-277 Range Voltage



PHYSICAL

| | |
|-------------------|-----------------------|
| Base: | GX23 |
| Shape: | PL |
| Finish: | Frost |
| Dimensions (In.): | MOL: 4.09 - MOD: 1.52 |
| Weight (Lbs.): | 0.11 |
| Material: | Aluminum |
| Housing Color: | White |

COMPLIANCE

| | |
|-----------------------------|------------------------------------|
| Safety Listing: | cULus - Listed; cULus - Classified |
| Location Rating: | Damp |
| Indoor/Outoor: | Indoor |
| DLC Approved: | No |
| BAA Compliant: | No |
| Enclosure Rating: | Enclosed Rated Lamp |
| Rated For Enclosed Fixture: | Yes |
| FCC Compliant: | Yes |
| NSF Approved: | Yes |
| RoHS Compliant: | Yes |
| Restrictions: | No Restrictions |