



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21433 - 5 Watt; PL LED; G24D Base; Frost Finish; Type A/B Dual Ballast; 4000K; 120-277 Range Voltage



ELECTRICAL

Technology:	LED
Watts:	5W
Volts:	120V-277V
Lumens:	650L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	13W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Ballast Type A/B/C :	Type A/B
Operating Position:	Universal
Power Factor :	0.9
Light Source:	LED
Voltage Type:	Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923409721
Each Quantity:	1
Each Dimensions:	1.77 x 1.77 x 4.21

INFO

Min Compartment Size:	Length 6.10 in. Width 6.10 in. Height: 7.87 in.
-----------------------	---

PHYSICAL

Base:	G24d (2-Pin)
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 3.9 - MOD: 1.52
Weight (Lbs.):	0.11
Material:	Aluminum
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Listed; cULus - Classified
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions