



ELECTRICAL

| | |
|---------------------------|--|
| Technology: | LED |
| Watts: | 11W |
| Volts: | 120V-277V |
| Lumens: | 1650L |
| CRI: | 80+ |
| CCT (Kelvins): | 30K/35K/40K/50K/65K - Soft White to Daylight |
| Beam Spread : | 170 |
| Hours Rated: | 50000 |
| Dimmable: | Yes-Dimmable - Only in Type A mode; Check Ballast MFG for Dimmer Compatibility |
| Dimmable Down To %: | 100 to 20 percent |
| Fluorescent Equivalent : | 21W/25W |
| Operating Temperature : | -20C (-4F) to +45C (+113F) |
| Ballasting Requirements : | Ballast required (Type A) or Ballast Bypass (Type B) |
| Lamp Ballast Type A/B/C : | Type A/B |
| Lamp End Type : | Single Ended; Double Ended |
| THD: | 20% |
| Power Factor : | 0.9 |
| Light Source: | LED |
| Voltage Type: | AC Only; Range Voltage |
| Warranty: | 5-Years |

PACKAGING

| | |
|------------------|---------------------|
| Each UPC: | 045923217616 |
| Each Quantity: | 1 |
| Each Dimensions: | 36.61 x 1.00 x 1.00 |

INFO

| | |
|--------------------|--------------------------------------|
| Installation Note: | Not for use in vapor tight fixtures. |
| Shatterproof Type: | PET Coated |

Project/Job Name:

Location:

Fixture Type:

Notes:

S21761 - 11 Watt T8 LED; 36-Inch; 30K/35K/40K/50K/65K CCT

Selectable; G13 Base; Ballast Type A/B; Frost Finish; 120-277
Ranged Voltage; Glass with PET Coating

- CCT Selectable



PHYSICAL

| | |
|-------------------|---------------------|
| Base: | Medium Bi Pin |
| Shape: | T8 |
| Finish: | Frost |
| Dimensions (In.): | MOL: 36.61 - MOD: 1 |
| Nominal Length: | 36 |
| Weight (Lbs.): | 0.39 |
| Material: | Glass |
| Housing Color: | White |

COMPLIANCE

| | |
|-----------------------------|---|
| Safety Listing: | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating: | Damp |
| Indoor/Outoor: | Indoor |
| DLC Approved: | Yes |
| DLC Classification: | Standard |
| DLC ID: | S-DTLYVZ |
| BAA Compliant: | No |
| Enclosure Rating: | Enclosed Rated Lamp |
| Rated For Enclosed Fixture: | Yes |
| FCC Compliant: | Yes |
| NSF Approved: | Yes |
| RoHS Compliant: | Yes |
| Restrictions: | No Restrictions |



S21761 - 11 Watt T8 LED; 36-Inch; 30K/35K/40K/50K/65K CCT
Selectable; G13 Base; Ballast Type A/B; Frost Finish; 120-277
Ranged Voltage; Glass with PET Coating

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
