



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V-277V
Lumens:	2200L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	170
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Dimmable Down To %:	100 to 20 percent
Fluorescent Equivalent :	25W/28W/30W/32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Ballast Type A/B/C :	Type A/B
Lamp End Type :	Single Ended; Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923217630
Each Quantity:	1
Each Dimensions:	48.67 x 1.00 x 1.00

INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated

Project/Job Name:

Location:

Fixture Type:

Notes:

S21763 - 15 Watt T8 LED; 48-Inch; 30K/35K/40K/50K/65K CCT

Selectable; G13 Base; Ballast Type A/B; Frost Finish; 120-277
Ranged Voltage; Glass with PET Coating

- CCT Selectable



PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Frost
Dimensions (In.):	MOL: 48.67 - MOD: 1
Nominal Length:	48
Weight (Lbs.):	0.49
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-BP3J9K
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S21763 - 15 Watt T8 LED; 48-Inch; 30K/35K/40K/50K/65K CCT
Selectable; G13 Base; Ballast Type A/B; Frost Finish; 120-277
Ranged Voltage; Glass with PET Coating

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
