



#### ELECTRICAL

Technology:	LED
Watts:	10W
Volts:	Ballast Dependent
Lumens:	1700L/1750L/1850L/1850L/1800L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	220
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Phase cut
Fluorescent Equivalent :	32W/30W/28W/25W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required, check compatibility
Lamp Ballast Type A/B/C :	Type A
THD:	<20%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	Ballast Dependent
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923219177
Each Quantity:	1
Each Dimensions:	48.00 x 1.18 x 1.18

#### INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated

Project/Job Name:

Location:

Fixture Type:

Notes:

**S21917** - 10 Watt; 4 Foot T8 LED; G13 Base; 30K/35K/40K/50K/65K CCT Selectable; Type A; Frost

- CCT Selectable



#### PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Frost
Dimensions (In.):	MOL: 47.78 - MOD: 1
Nominal Length:	48
Weight (Lbs.):	0.47
Material:	Glass
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-6222FT
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions