Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S23135 - 200/150/100 Watt; 30K/40K/50K CCT; Field Selectable LED; Corncob; Mogul Extended Base; 120-277 Ranged Voltage; 500 Watt HID Replacement

- Wattage Selectable
- CCT Selectable

RoHS COMPLIANT | FC | DIMMABLE | DAMP LOCATION | DLC LISTED

ELECTRICAL

Technology:	LED
Watts:	200W/150W/100W
Volts:	120V-277V
Lumens:	33380L/26081L/18124L
CRI:	80+
R9 Value :	23
CCT (Kelvins):	30K/40K/50K - Soft White to Natural Light
Beam Spread :	280
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only dimmable through wattage selection switch on lamp
Dimming Type :	Step Dimming
HID Equivalent :	500W
Operating Temperature :	-40C (-40F) to +50C (+122F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 6KV
THD:	<20%
Power Factor :	0.99
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923231353
Each Quantity:	1
Each Dimensions:	5.91 x 5.91 x 12.40

PHYSICAL

Base:	Mogul Extended
Shape:	Corncob
Finish:	White
Lens Finish:	Clear
Lens Material:	Polycarbonate (PC)
Dimensions (In.):	MOL: 10.6 - MOD: 5.6
Weight (Lbs.):	2.86
Material:	Aluminum / Polycarbonate (PC)
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Listed; cULus - Classified
Location Rating:	Damp
Indoor/Outoor:	Indoor and Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-P12TX1
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP54
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Additional Info:	Decibels: 47.5dB(A)
Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 18.50 in. Width:12.60 in. Height: 12.60 in.