



ELECTRICAL

Technology:	LED
Watts:	16W
Volts:	Ballast Dependent
Lumens:	1700L/1700L/1800L/1800L
CRI:	80+
CCT (Kelvins):	30K/40K/50K/65K - Soft White to Daylight
Beam Spread :	240
Hours Rated:	36000
Dimmable:	Yes-Dimmable - Only Dimmable with Compatible Dimming Ballasts
Dimmable Down To %:	100 to 10 percent
Fluorescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required, check compatibility
Lamp Ballast Type A/B/C :	Type A
Lamp End Type :	Double Ended
THD:	<25%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	Ballast Dependent
Warranty:	3-Years

PACKAGING

Each UPC:	045923265006
Each Quantity:	1
Each Dimensions:	47.87 x 2.99 x 1.69

INFO

Specification Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated

Project/Job Name:

Location:

Fixture Type:

Notes:

S26500 - 16 Watt T12 LED; 3K/4K/5K/65K CCT Selectable; G13 Base; 2-Pack

- CCT Selectable



PHYSICAL

Base:	Medium Bi Pin
Shape:	T12
Finish:	Frost
Dimensions (In.):	MOL: 47.74 - MOD: 1.42
Weight (Lbs.):	0.67
Material:	Glass
Leg Spacing:	0.51
Housing Color:	White

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Open Rated Lamp
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions