



#### ELECTRICAL

Technology:	LED
Watts:	6W
Volts:	120V-277V
Lumens:	600L/625L/650L/650L/625L
CRI:	80+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	360
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	13W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	<20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923287305
Each Quantity:	1
Each Dimensions:	1.46 x 0.98 x 7.40

Project/Job Name:

Location:

Fixture Type:

Notes:

**S28730** - 6 Watt LED PL 2-PIN; GX23 Base;  
27K/30K/35K/40K/50K CCT Selectable; 120-277 Volt; Type B;  
Ballast Bypass

- CCT Selectable



#### PHYSICAL

Base:	GX23
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 7.09 - MOD: 1.27
Weight (Lbs.):	0.11
Material:	Polycarbonate (PC)
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cETLus - Classified
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions



**S28730** - 6 Watt LED PL 2-PIN; GX23 Base;  
27K/30K/35K/40K/50K CCT Selectable; 120-277 Volt; Type B;  
Ballast Bypass

## ACCESSORIES

---



**S8000** 5 Watt LED Emergency Driver; 120-277 Volts

---



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt

---