



#### ELECTRICAL

Technology:	LED
Watts:	9.5W
Volts:	120V-277V
Lumens:	1100L/1150L/1200L
CRI:	80+
CCT (Kelvins):	30K/35K/40K - Warm to Cool White
Beam Spread :	360
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Triac
Fluorescent Equivalent :	18W/26W/32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Ballast Type A/B/C :	Type A/B
Operating Position:	Universal
THD:	<20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923298547
Each Quantity:	1
Each Dimensions:	1.46 x 1.46 x 7.01

Project/Job Name:

Location:

Fixture Type:

Notes:

**S29854** - 9.5 Watt LED PL; 30K/35K/40K CCT Selectable; G24q Base; Type A/B; 120-277 Volt

- CCT Selectable



#### PHYSICAL

Base:	G24q (4-Pin)
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 6.9 - MOD: 1.4
Weight (Lbs.):	0.22
Material:	Aluminum / Plastic
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



**S29854** - 9.5 Watt LED PL; 30K/35K/40K CCT Selectable; G24q Base; Type A/B; 120-277 Volt

## ACCESSORIES

---



**S8000** 5 Watt LED Emergency Driver; 120-277 Volts

---



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt

---