



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S29855 - 9 Watt LED PL; 27K/3K/35K/4K CCT Selectable; G24d Base; Type B; 120-277 Volt

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	9W
Volts:	120V-277V
Lumens:	1050L/1100L/1150L/1200L
CRI:	80+
CCT (Kelvins):	27K/30K/35K/40K - Warm to Cool White
Beam Spread :	360
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	18W/26W/32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	<20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923298554
Each Quantity:	1
Each Dimensions:	1.46 x 1.46 x 7.01

PHYSICAL

Base:	G24d (2-Pin)
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 6.9 - MOD: 1.4
Weight (Lbs.):	0.22
Material:	Aluminum / Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S29855 - 9 Watt LED PL; 27K/3K/35K/4K CCT Selectable; G24d Base; Type B; 120-277 Volt

ACCESSORIES

	S8000	5 Watt LED Emergency Driver; 120-277 Volts
--	--------------	--

	S8002	10 Watt LED Emergency Driver; 120-277 Volt
--	--------------	--
