



ELECTRICAL

Technology:	LED
Watts:	9.5W
Volts:	Ballast Dependent
Lumens:	1100L/1150L/1200L
CRI:	80+
CCT (Kelvins):	30K/35K/40K - Warm to Cool White
Beam Spread :	360
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only Dimmable with Compatible Dimming Ballasts
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Triac
Fluorescent Equivalent :	18W/26W/32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required, check compatibility
Lamp Ballast Type A/B/C :	Type A
Operating Position:	Universal
THD:	<20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	Ballast Dependent
Warranty:	5-Years

PACKAGING

Each UPC:	045923298561
Each Quantity:	1
Each Dimensions:	1.46 x 1.46 x 7.01

Project/Job Name:

Location:

Fixture Type:

Notes:

S29856 - 9.5 Watt LED PL; 30K/35K/40K CCT Selectable; G24q Base; Type A

- CCT Selectable



PHYSICAL

Base:	G24q (4-Pin)
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 6.9 - MOD: 1.4
Weight (Lbs.):	0.2
Material:	Aluminum / Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S29856 - 9.5 Watt LED PL; 30K/35K/40K CCT Selectable; G24q Base; Type A

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
