



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S39918 - 15 Watt 4 Foot T8 LED; 3500K CCT; Medium Bi Pin Base; Ballast Bypass; Single or Double Ended Wiring; 120-277 Volt



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V-277V
Lumens:	2100L
CRI:	80+
CCT (Kelvins):	3500K - Neutral White
Beam Spread :	210
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	25W/28W/30W/32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	<20%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923399183
Each Quantity:	1
Each Dimensions:	47.78 x 1.00 x 1.00

PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Gloss White
Dimensions (In.):	MOL: 47.78 - MOD: 1
Nominal Length:	48
Weight (Lbs.):	0.46
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outdoor:	Indoor and Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-2VHVDVL
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Installation Note:	Not for use in vapor tight fixtures.
--------------------	--------------------------------------



S39918 - 15 Watt 4 Foot T8 LED; 3500K CCT; Medium Bi Pin Base;
Ballast Bypass; Single or Double Ended Wiring; 120-277 Volt

ACCESSORIES



S8000

5 Watt LED Emergency Driver; 120-277 Volts



S8002

10 Watt LED Emergency Driver; 120-277 Volt
