



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S49978R1** - 14 Watt; 4 Foot T8 LED; G13 Base; 5000K; Type A



#### ELECTRICAL

Technology:	LED
Watts:	14W
Volts:	Ballast Dependent
Lumens:	2200L
CRI:	80+
CCT (Kelvins):	5000K - Natural Light
Beam Spread :	210
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Dimmable Down To %:	100 to 20 percent
Incandescent Equivalent :	175W
Fluorescent Equivalent :	32W/30W/28W/25W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required, check compatibility
Lamp Ballast Type A/B/C :	Type A
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	Ballast Dependent
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923403200
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10

#### INFO

Installation Note:	Not for use in vapor tight fixtures.
--------------------	--------------------------------------

#### PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Gloss White
Dimensions (In.):	MOL: 47.78 - MOD: 1.1
Nominal Length:	48
Weight (Lbs.):	0.38
Material:	Glass / Steel
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-5GVY6Y
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions