



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S8750 - 8 Watt LED PL; GU24 Base; 27K/30K/35K/40K/50K CCT Selectable; Type B Ballast Bypass; 120-277 Volt

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	8W
Volts:	120V-277V
Lumens:	950L/975L/1000L/1050L/1050 L
CRI:	80+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	18W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	<20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923087509
Each Quantity:	1
Each Dimensions:	1.65 x 1.65 x 7.28

PHYSICAL

Base:	Bi Pin GU24
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 6.5 - MOD: 1.38
Weight (Lbs.):	0.24
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	Not For Sale In: CA