



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S8791 - 20 Watt LED A21; High lumen output; 2700K; Medium base; 120 Volt; 90 CRI; Dimmable



ELECTRICAL

Technology:	LED
Watts:	20W
Volts:	120V
Lumens:	2040L
CRI:	90+
Rg Value :	38
CCT (Kelvins):	2700K - Warm White
Beam Spread :	280
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Adaptive Phase
Incandescent Equivalent :	125W
Fluorescent Equivalent :	40W
Operating Temperature :	-25C (-13F) to +40C (+104F)
Candlepower :	18.2
Light Source:	LED
Warranty:	5-Years

PACKAGING

Each UPC:	045923087912
Each Quantity:	1
Each Dimensions:	2.76 x 2.76 x 5.51

INFO

Min Compartment Size:	Width: 6.00 in. Height: 8.50 in.
-----------------------	----------------------------------

PHYSICAL

Base:	Medium
Shape:	A21
Finish:	White
Dimensions (In.):	MOL: 5 - MOD: 2.44
Weight (Lbs.):	0.43
Material:	Die-Cast Aluminum / PC
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S8791 - 20 Watt LED A21; High lumen output; 2700K; Medium base; 120 Volt; 90 CRI; Dimmable

DIMMER COMPATIBILITY

Leviton	6674
Satco	86/103
Legrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Leviton	DSM10-1LZ
Lutron	DVCL-153P
Lutron	GT-5NEM
Lutron	GTJ-5NEM
Lutron	HQRA-6CL
Lutron	HQRD-HN6BRL
Lutron	HW-RPM-4A-120
Lutron	HW-RPM-4U-120
Lutron	HWD-6ND
Lutron	HWI-WPM-6D-120
Leviton	IPL06-10Z
Lutron	LECL-153PH
Lutron	LQRJ-WPM-6P
Lutron	LQSE-4A-120-D
Lutron	LQSE-4A1-D
Lutron	MACL-153M
Lutron	MRF2S-6CL
Lutron	MSCL-OP153M
Lutron	NTRP-250
Lutron	PD-6WCL
Lutron	PHPM-WBX-120

Lutron	RRD-6CL
Lutron	RRD-HN6BRL
Eaton	TALo6P-C2