

Allusion LED Line with Smooth Warm Dimming

Introducing TCP's latest offering of Allusion LED Line—the "incandescent-like" LEDs that offer a unique dimming profile, replicating true incandescent/halogen dimming.

Reasons to choose the Allusion LED Lamps from TCP

- Instant energy savings - up to 85% more efficient than incandescent/halogen replacements
- Long life of 25,000/30,000 (SL16) hours minimizes replacement and maintenance costs
- Smooth warm dimming creates the perfect atmosphere
- UL approved for damp locations* - can be used outdoors when protected from elements. Can withstand humidity indoors/outdoors
- Shatter resistance lowers the risk of injury and breakage

Ideal Applications

- Table Lamps
- Floor Lamps
- Sconces
- Ceiling Fixtures
- Chandeliers
- Decorative
- Track Lights
- Recessed Downlights

Specifications

Voltage ..... 120VAC/ 12 VAC (MR16)
Input Line Frequency..... 50/60Hz
Lamp Life (Rated) 25,000/30,000 (SL16)
Minimum Starting Temp .....-22°F/-30°C
Maximum Operating Temp.....45°C

CRI..... 80
Color Temperatures..... 3000K to 2000K/
.....3000K to 1800K (MR16/DL)/
.....2700K to 2000K (A19)

TCP®
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

*WET LOCATION
PAR38, PAR30 and PAR20 lamps UL approved for wet location

c UL us LISTED

RoHS COMPLIANT

5 YEAR WARRANTY
*Troffer warranty is 5yrs/50,000hrs

Allusion LED Lamps

Specifications


A19


BR30


PAR38
40°/25°
Beam Angles


PAR30
40°/25°
Beam Angles


PAR20
40°/25°
Beam Angles


MR16 GU5.3
20°
Beam Angle


SL16 Starlight
110° Beam Angle


5"/6" Recessed Downlight

ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	WATTAGE EQUIVALENT	LUMENS	LPW	CRI	COLOR TEMPERATURE	BEAM ANGLE	MOL (inches)	DIA (inches)	BASE
LED A19 60W Equivalent												
LED9A19DA	LED 9W A19 27K Allusion	120V	9	60	650	72.2	>80	2700K to 2000K	-	4.6	2.4	E26
LED BR30 65W Equivalent												
LED10BR30DA	LED 10W BR30 27K Allusion	120V	10	65	675	67.5	>80	3000K to 2000K	-	5.4	3.8	E26
LED PAR38 90W Equivalent												
L15P38DNFLA	LED 15W PAR38 30K Allusion NFL	120V	12.5	90	975	78.00	>80	3000K to 2000K	25°	5.4	4.75	E26
L15P38DFLA	LED 15W PAR38 30K Allusion FL	120V	12.5	90	975	78.00	>80	3000K to 2000K	40°	5.4	4.75	E26
LED PAR38 100W Equivalent • PHASE OUT												
LED15P38DA	LED 15W PAR38 30K Allusion NFL	120V	15	100	975	65	>80	3000K to 2000K	25°	5.4	4.75	E26
LED PAR30 90W Equivalent												
L15P30DNFLA	LED 15W PAR30 30K Allusion NFL	120V	12.5	90	950	76.00	>80	3000K to 2000K	25°	4.7	3.8	E26
L15P30DFLA	LED 15W PAR30 30K Allusion FL	120V	12.5	90	950	76.00	>80	3000K to 2000K	40°	4.7	3.8	E26
LED PAR20 50W Equivalent												
L7P20DNFLA	LED 7W PAR20 30K Allusion NFL	120V	6.5	50	525	80.77	>80	3000K to 2000K	25°	3.4	2.5	E26
L7P20DFLA	LED 7W PAR20 30K Allusion FL	120V	6.5	50	525	80.77	>80	3000K to 2000K	40°	3.4	2.5	E26
LED MR16 35W Equivalent												
L712VMR16DNFLA	LED 7W MR16 30K Allusion NFL	12V	6	35	350	58.33	>80	3000K to 1800K	20°	1.9	2.0	5.3
LED SL16 Starlight												
L15SL16D30A	LED 13W SL16 30K Allusion	120V	13	—	1200	92.30	>80	3000K to 2000K	110°	3.8	6.3	E26
LED 5"/6" Downlight 65W Equivalent												
LED10DR56DA	LED 11W 5"/6" Recessed Downlight Allusion	120V	11	65	1100	100	>80	3000K to 1800K	-	3.0	7.5	E26

For the most up-to-date specs, please visit www.tcpi.com

TCP®
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

PAR38, PAR30 and PAR20 lamps UL approved for wet location

c UL us LISTED

RoHS COMPLIANT

5 YEAR WARRANTY
*Troffer warranty is 5yrs/50,000hrs

Allusion LED Lamps

Dimmer Compatibility

E26 SUGGESTED DIMMER COMPATIBILITY	
MANUFACTER	MODEL NUMBER
Leviton	R50-IPL06-10M
	R61-06674-P0I
Lutron	CTCL-153PDH-WH
	TGCL-153PH-WH
	DVWCL-153PH-WH

MR16 SUGGESTED DIMMER COMPATIBILITY	
MANUFACTER	MODEL NUMBER
Leviton	Sureslide 6615P
Lutron	Diva DVLV-600P
	Divs DVELV-300P
	Skylark SLEV-300P
	Skylark SLV-600P
	Nova NELV-450
	Nova NTELV-600
	MALV-600
	VERTI VTELV-600M
Cooper	DAL06P - All load dimmer
	SAL06P

For the most up-to-date specs, please visit www.tcpi.com

TCP®
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

©TCP MAY 2024/WF225757

* WET LOCATION
PAR38, PAR30 and PAR20 lamps UL approved for wet location

c UL us LISTED

RoHS COMPLIANT

5 YEAR WARRANTY
*Troffer warranty is 5yrs/50,000hrs

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:	Catalog Number:
Date:	Type:
Model:	Notes:
Project:	
Rep:	

TCP® we know light.™

For more information on the quality and care TCP can deliver, call us at 800.324.1496 or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516